

SUB WOOFER SYSTEM



The B218 is efficiently tuned frontloaded cabinet. It houses double, long-excursion, eighteen inch cone drivers. Primarily it complements as a low extension in the EA systems product line.

This loudspeaker is suitable for multiple setups. In upright position combined with a FT12 top loudspeaker or up to 4 cabinets stacked per side (all front or cardioid) or as an end-fire setup for a solid deep bass with a heavy punch.

FEATURES

- Compact Vented sub-bass
- Direct radiating dual 18"(460mm) sub-woofer
- High temperature 4" (100mm) long excursion voice coil

APPLICATIONS

- Applied for live club performance
- Large entertainment low frequency sound reinforcement
- Multi-purpose hall low frequency sound reinforcement

TECHNICAL SPECIFICATIONS

FREQUENCY RESPONSE	35HZ - 300HZ(±3dB)
DRIVERS	2 X 18"(460mm) / 4" voice coil LF
RATED POWER	1200W RMS, 4800W peak
SENSITIVITY	103 dB, 1W / 1M
MAXIMUM SPL	133 dB continuous, 139 dB peak
IMPEDANCE	4 ohms nominal
PROTECTIVE GRILL	Black perforated steel incl. cloth
CONNECTORS	2 X Speakon NL4
DIMENSIONS	(W)1166mm X (D)743mm X (H)542mm
WEIGHT	84 kg

CONFIGURATION