

SUB WOOFER SYSTEM



The B15 is a front loaded single 15 inch low frequency enclosure, useful for a wide range of applications. Suitable for small events from 25 people up to a big event with 750 people.

This sub enclosure is combinable with all the EA systems FT and Line-Array products.

FEATURES

- Compact vented sub-bass
- Direct radiating 15" (460mm) sub-woofer
- High temperature 4" (100mm) voice coil

APPLICATIONS

- Applied for live club performance, large place of entertainment part low-frequency sound reinforcement.
- Large entertainment balcony low frequency sound reinforcement
- Multi-purpose hall low frequency sound reinforcement

TECHNICAL SPECIFICATIONS

FREQUENCY RESPONSE	40 HZ_30()HZ(i3dB)
DRIVER	1 X 15"(3 85mmn) / 4"voice coil LF
RATED POWER	600W RMS, 2400W peak
SENSITIVITY	99 dB 1W / 1M
MAXIMUM SPL	126 dB continuous, 132 dB peak
IMPEDANCE	8 ohms nominal
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 X Speakon NL4
DIMENSIONS	(W) 500mm X (D) 572mm X (H)450mm
WEIGHT	32.4kg

CONFIGURATION

